



FLOW RATE WITH PRESSURE DROP (FULLY OPEN POSITION)			
5 PSI	10 PSI	20 PSI	40 PSI
5.5 GPM	7.7 GPM	10.9 GPM	15.5 GPM
FLOW RATE WITH PRESSURE DROP (FULLY OPEN POSITION)			
0.3 BAR	0.7 BAR	2.1 BAR	2.8 BAR
20.8 L/MIN	29.1 L/MIN	41.3 L/MIN	58.7 L/MIN

*\*INDIVIDUAL PARTS NOT AVAILABLE FOR SALE\**

**SPECIFICATIONS:**

- MAXIMUM PRESSURE RATING: 290 PSI (20 BAR)
- WETTED MATERIALS: POLYPROPYLENE, NYLON, STAINLESS STEEL, FKM

**FEATURES INCLUDE:**

- MODULAR CLIPPED BODY ALLOWS FOR TOOL FREE ASSEMBLY OF VARIOUS ACCESSORIES AND MANIFOLD COMPONENTS
- MANUAL CONTROL OF SYSTEM PRESSURE
- SPRING LOADED PLUNGER PROTECTS SYSTEM FROM LARGE PRESSURE SPIKES BY RELIEVING EXCESS FLOW
- DESIGNED FOR USE WITH C530AM AND C530AEC MANIFOLDS
- STAINLESS STEEL STEM PROVIDES EXCELLENT DURABILITY AND CHEMICAL RESISTANCE
- OUTLET CONNECTIONS AVAILABLE IN QUICK CONNECT HOSE BARBS; REFER TO PL45529
- INLET OPTIONS AVAILABLE IN CLIPPED HOSE BARB AND VARIOUS THREAD SIZES; REFER TO PL191016

**DESCRIPTION:**

CLIPPED C118560  
PRESSURE RELIEF  
VALVE ASSEMBLY



REVISION NO.	1	Data Sheet No.	
REFERENCE:	9/12/24	DSC118560	
SHEET:	1 OF 1	DWG SIZE:	A