



QUICK TEEJET® LUGS ACCEPT ANY QUICK TEEJET CAP AND PROVIDE AUTOMATIC ALIGNMENT OF TIPS

TO INSTALL ASSEMBLY DRILL 3/8" (9.5 mm) DIAMETER HOLE IN PIPE, DEBURR, THEN INSERT NOZZLE BODY INLET AND CLAMP ASSEMBLY IN PLACE. FOR X7 VERSIONS USE A HOLE DIAMETER OF 7.0 mm.

BODY ASSEMBLY No.	"A"	"B"	"C"	TO CLAMP ON
QJB17560A-1/2-AC	4" (102 mm)	3 7/16" (86 mm)	1 15/16" (49 mm)	1/2" Pipe
QJB17560A-1/2X7-AC	4" (102 mm)	3 7/16" (86 mm)	1 15/16" (49 mm)	1/2" Pipe
QJB17560A-3/4-AC	4 1/16" (103 mm)	3 7/16" (86 mm)	2" (51 mm)	3/4" Pipe
QJB17560A-1-AC	4 3/16" (106 mm)	3 7/16" (86 mm)	2 5/16" (59 mm)	1" Pipe
QJB17560A-20mm-AC	3 15/16" (100 mm)	3 7/16" (86 mm)	1 7/8" (48 mm)	20mm O.D. Tubing
QJB17560A-20mmX7-AC	3 15/16" (100 mm)	3 7/16" (86 mm)	1 7/8" (48 mm)	20mm O.D. Tubing
QJB17560A-25mm-AC	4 1/16" (103 mm)	3 7/16" (86 mm)	1 15/16" (49 mm)	25 mm O.D. Tubing

Note: "A", "B", & "C" dimensions are approximate.

FEATURES:

- FAST AND EASY WAY TO MOUNT SPRAY NOZZLES TO BOOMS AND HEADERS.
- HINGED UPPER CLAMP REDUCES ASSEMBLY TIME.
- ALLOWS FOR QUICK CHANGE OF SPRAY TIPS.
- DRIP-FREE POSITIVE SHUT-OFF.
- NOTCHED INLET TUBE PREVENTS SEDIMENT BUILDUP IN BOOM.
- MADE OF CORROSION RESISTANT MATERIALS.
- STANDARD O-RING MADE OF BUNA-N.
- STANDARD DIAPHRAGM MADE OF POLYURETHANE.
- MINIMUM 55 PSI (3.75 Bar) OPENING AIR PRESSURE
- MAXIMUM 115 PSI (8 Bar) LIQUID PRESSURE
- HEX SOCKET IN CENTER OF UPPER CLAMP PERMITS ATTACHMENT TO FLAT SURFACE USING CUSTOMER SUPPLIED FASTENER. ACCEPTS 5/16" OR M8 HEX.
- CLAMP ASSEMBLY WILL FIT INSIDE COMMON CHANNELS USED FOR SPRAY BOOMS.
- THE 56720 AIR CHEMSAVER® IS DESIGNED AS A PNEUMATIC SHUT-OFF VALVE FOR USE ON QUICK TEEJET® NOZZLE ASSEMBLIES. AIR PRESSURE IS USED TO OPEN THE VALVE AND A SPRING IS USED TO CLOSE THE VALVE.
- SEE DS556720 FOR FURTHER INFORMATION.

HOW TO ORDER:

FOR DIAPHRAGM QUICK TEEJET® BODY ASSEMBLY (DOES NOT INCLUDE CAP, GASKET, TIP OR STRAINER)

EXAMPLES: QJB17560A-1/2-AC QUICK TEEJET® NOZZLE BODY ASSEMBLY
QJB17560A-20MM-AC QUICK TEEJET® NOZZLE BODY ASSEMBLY

DESCRIPTION:
QJB17650A-AC HINGED CLAMP
WET BOOM DIAPHRAGM
NOZZLE BODY ASSEMBLY WITH
(1/2", 3/4", 1", 20mm, & 25mm)
DIAPHRAGM TYPE AIR CHEMSAVER®
SHUT-OFF VALVE
(BSPT CONNECTION)



Spraying Systems Co.®

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 1

Ref.

Data Sheet No.

DSQJ17560A-AC

SHEET OF