



**FEATURES**

- DESIGNED FOR USE WITH QUICK TEEJET® VARI-SPACING CLAMPS - SEE DS21386-4
- USED WITH QUICK TEEJET® CAPS
- HOSE SHANK AVAILABLE AS SINGLE, OR DOUBLE IN 3/8", 1/2", AND 3/4" SIZES
- MADE OF CORROSION RESISTANT MATERIALS
- DRIP FREE POSITIVE SHUT-OFF
- LOW PROFILE DESIGN ALLOWS MAXIMUM PROTECTION AGAINST DAMAGE
- MAXIMUM OPERATING PRESSURE OF 150 PSI (10 BAR)
- ALLOWS MANUAL SHUT OFF OF INDIVIDUAL NOZZLE BODIES
- WITH RETAINING RING IN FULLY OPEN POSITION (TURN COUNTERCLOCKWISE), FUNCTIONS LIKE A STANDARD 10 PSI (0.7 BAR) DIAPHRAGM CHECK VALVE
- WITH RING IN FULLY CLOSED POSITION (TURN CLOCKWISE), ALL FLOW THROUGH NOZZLE BODY IS SHUT OFF

STYLE	BODY No.	"A" DIM. (APPROX.)	"B" DIM. (APPROX.)	"C" DIM. (APPROX.)
SINGLE	22251-311-375-MC	2" (51 mm)	3" (76 mm)	1 7/16" (36 mm)
	22251-311-500-MC	2" (51 mm)	3" (76 mm)	1 7/16" (36 mm)
	22251-311-750-MC	2 5/16" (59 mm)	3" (76 mm)	1 7/16" (36 mm)
DOUBLE	22252-312-375-MC	3 1/8" (79 mm)	3" (76 mm)	1 7/16" (36 mm)
	22252-312-500-MC	3 1/8" (79 mm)	3" (76 mm)	1 7/16" (36 mm)
	22252-312-750-MC	3 3/4" (95 mm)	3" (76 mm)	1 7/16" (36 mm)

**DESCRIPTION:**

QJ300 SERIES HOSE SHANK NOZZLE BODIES WITH 58140 MANUAL CHEMSAVER® INDIVIDUAL TIP SHUT-OFF



**Spraying Systems Co.®**

Spray Nozzles and Accessories  
P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.

Ref.

DATA SHEET  
DSQJ300-MC  
SHEET OF