



FEATURES:

- COMPACT DESIGN FOR EASIER MOUNTING AND LESS INTERFERENCE WITH BOOM STRUCTURE.
- QUICK HAND INDEXING WITH CHOICE OF THREE OR FIVE OUTLET TURRET.
- ALLOWS FOR RAPID CHANGE OF SPRAY TIPS WITH USE OF QUICK TEEJET CAPS.
- POSITIVE SHUT-OFF BETWEEN EACH SPRAY POSITION.
- MADE OF CORROSION RESISTANT MATERIALS.
- WETTED PARTS MADE OF NYLON, ACETAL AND EPDM OR VITON.
- STANDARD O-RINGS AND DIAPHRAGM MADE OF EPDM.
- OPTIONAL O-RINGS AND DIAPHRAGM MADE OF VITON.
- STANDARD OPENING PRESSURE - 10 PSI (0.7 bar)
- MAXIMUM OPERATING PRESSURE - 300 PSI (20 bar).
- FLOW RATE: 1.80 GPM (6.8 l/min) WITH A 5 PSI (0.34 bar) PRESSURE DROP.
- AVAILABLE WITH SINGLE OR DOUBLE HOSE SHANK CONNECTIONS FOR 1/2", 3/4" AND 1" (I.D.) HOSE SIZES.
- BODY FEATURES MOUNTING LUG FOR USE WITH TEEJET VARI-SPACING CLAMPS FOR ATTACHING TO DRY BOOM SPRAYERS.
- FOR MORE INFORMATION ON TEEJET VARI-SPACING CLAMPS SEE DATA SHEET 21386-4.

PART NO.	NUMBER OF OUTLETS	CONNECTION TYPE	"A"
QJ35*-500-1(R)-NYB	3 OR 5	1/2" SINGLE HOSE SHANK	1.88" (48 mm)
QJ35*-750-1(R)-NYB	3 OR 5	3/4" SINGLE HOSE SHANK	2.00" (51 mm)
QJ35*-1000-1(R)-NYB	3 OR 5	1" SINGLE HOSE SHANK	2.13" (54 mm)
QJ35*-500-2-NYB	3 OR 5	1/2" DOUBLE HOSE SHANK	2.88" (73 mm)
QJ35*-750-2-NYB	3 OR 5	3/4" DOUBLE HOSE SHANK	3.12" (79 mm)
QJ35*-1000-2-NYB	3 OR 5	1" DOUBLE HOSE SHANK	3.38" (86 mm)

Note: All dimensions are approximate. For single hose shank versions an "R" in the part number specifies right-handed hose shank orientation (as viewed with turret facing you). If "R" is not specified a left-handed configuration will be provided.

HOW TO ORDER:

QJ355-500-1-NYB QUICK TEEJET NOZZLE BODY ASSEMBLY

QJ355-500-1-NYB-VI QUICK TEEJET NOZZLE BODY ASSEMBLY
(VITON DIAPHRAGM AND O-RINGS)

DESCRIPTION:
QJ350 DRY BOOM
DIAPHRAGM CHECK VALVE
QUICK TEEJET®
TURRET NOZZLE BODY

OBSOLETE



Spraying Systems Co.®

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 1

Ref.

DATA SHEET

QJ350-DB

SHEET OF