



TO INSTALL ASSEMBLY DRILL 3/8" (9.5 mm) DIAMETER HOLE IN PIPE, DEBURR, THEN INSERT NOZZLE BODY INLET AND CLAMP ASSEMBLY IN PLACE.

PART NO.	NUMBER OF OUTLETS	TO CLAMP ON	"A"	"B"	"C"
QJ35*-1-NYB	3 OR 5	1" PIPE	1.24" (32 mm)	2.52" (64 mm)	4.41" (112 mm)
QJ35*-3/4-NYB	3 OR 5	3/4" PIPE	1.07" (27 mm)	2.25" (57 mm)	4.30" (109 mm)
QJ35*-1/2-NYB	3 OR 5	1/2" PIPE	1.10" (28 mm)	2.25" (57 mm)	3.91" (99 mm)
QJ35*-20mm-NYB	3 OR 5	20mm O.D. Tubing	1.07" (27 mm)	2.25" (57 mm)	3.88" (99 mm)

Note: All dimensions are approximate.

FEATURES:

- COMPACT DESIGN FOR EASIER MOUNTING AND LESS INTERFERENCE WITH BOOM STRUCTURE.
- QUICK HAND INDEXING WITH CHOICE OF THREE OR FIVE OUTLET TURRET.
- HINGED UPPER CLAMP AND SINGLE SCREW REDUCES ASSEMBLY TIME.
- ALLOWS FOR RAPID CHANGE OF SPRAY TIPS WITH USE OF QUICK TEEJET CAPS.
- POSITIVE SHUT-OFF BETWEEN EACH SPRAY POSITION.
- NOTCHED INLET TUBE ALLOWS FOR MORE COMPLETE BOOM DRAINAGE AND REDUCES SEDIMENT BUILDUP.
- MADE OF CORROSION RESISTANT MATERIALS.
- WETTED PARTS MADE OF NYLON, ACETAL AND EPDM OR VITON.
- STANDARD O-RINGS AND DIAPHRAGM MADE OF EPDM.
- OPTIONAL O-RINGS AND DIAPHRAGM MADE OF VITON.
- STANDARD OPENING PRESSURE - 10 PSI (0.7 bar)
- MAXIMUM OPERATING PRESSURE - 300 PSI (20 bar).
- FLOW RATE: 1.80 GPM (6.8 l/min) WITH A 5 PSI (0.34 bar) PRESSURE DROP.
- AVAILABLE FOR 20mm TUBING; 1/2", 3/4", AND 1" PIPE.
- HEX SOCKET IN CENTER OF UPPER CLAMP PERMITS ATTACHMENT TO FLAT SURFACE USING CUSTOMER SUPPLIED FASTENER.
- CLAMP ASSEMBLY WILL FIT INSIDE COMMON CHANNELS USED FOR SPRAY BOOMS.

HOW TO ORDER:

QJ355-1-NYB QUICK TEEJET NOZZLE BODY ASSEMBLY

QJ355-1-NYB-VI QUICK TEEJET NOZZLE BODY ASSEMBLY
(VITON DIAPHRAGM AND O-RINGS)

DESCRIPTION:

QJ350 WET BOOM
DIAPHRAGM CHECK VALVE
QUICK TEEJET®
TURRET NOZZLE BODY

OBSOLETE



Spraying Systems Co.®

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 1

Ref.

DATA SHEET

QJ350-WB

SHEET OF