



TO INSTALL ASSEMBLY DRILL .280" (7 mm) DIAMETER HOLE IN PIPE, DEBURR, THEN INSERT NOZZLE BODY INLET AND CLAMP ASSEMBLY IN PLACE.

| PART NO. | NUMBER OF OUTLETS | TO CLAMP ON | "A" | "B" | "C" |
|-----------------|-------------------|------------------|------------------|------------------|------------------|
| QJ35*-1/2X7-AC | 3 OR 5 | 1/2" PIPE | 1.10" (28 mm) | 2.25" (57 mm) | 3.91" (99 mm) |
| QJ35*-20mmX7-AC | 3 OR 5 | 20mm O.D. Tubing | 1.07" (27 mm) | 2.25" (57 mm) | 3.88" (99 mm) |

Note: All dimensions are approximate.

FEATURES:

- COMPACT DESIGN FOR EASIER MOUNTING AND LESS INTERFERENCE WITH BOOM STRUCTURE.
- QUICK HAND INDEXING WITH CHOICE OF THREE OR FIVE OUTLET TURRET.
- HINGED UPPER CLAMP AND SINGLE SCREW REDUCES ASSEMBLY TIME.
- ALLOWS FOR RAPID CHANGE OF SPRAY TIPS WITH USE OF QUICK TEEJET CAPS.
- POSITIVE SHUT-OFF BETWEEN EACH SPRAY POSITION.
- NOTCHED INLET TUBE ALLOWS FOR MORE COMPLETE BOOM DRAINAGE AND REDUCES SEDIMENT BUILDUP.
- MADE OF CORROSION RESISTANT MATERIALS.
- WETTED PARTS MADE OF NYLON, ACETAL AND POLYURETHANE
- STANDARD O-RINGS AND DIAPHRAGM MADE OF POLYURETHANE.
- MINIMUM PRESSURE 55 PSI (3.75 Bar) OPENING AIR PRESSURE
- MAXIMUM 115 PSI (8 Bar) LIQUID PRESSURE
- FLOW RATE: 1.80 GPM (6.8 l/min) WITH A 5 PSI (0.34 bar) PRESSURE DROP.
- AVAILABLE FOR 20mm TUBING; 1/2" PIPE.
- HEX SOCKET IN CENTER OF UPPER CLAMP PERMITS ATTACHMENT TO FLAT SURFACE USING CUSTOMER SUPPLIED FASTENER.
- CLAMP ASSEMBLY WILL FIT INSIDE COMMON CHANNELS USED FOR SPRAY BOOMS.
- THE 56720 AIR CHEMSAVER® IS DESIGNED AS A PNEUMATIC SHUT-OFF VALVE FOR USE ON QUICK TEEJET® NOZZLE ASSEMBLIES. AIR PRESSURE IS USED TO OPEN THE VALVE AND A SPRING IS USED TO CLOSE THE VALVE.

HOW TO ORDER:

QJ355-1/2X7-AC QUICK TEEJET® NOZZLE BODY ASSEMBLY

DESCRIPTION:
QJ350X7 WET BOOM
AIR CHEMSAVER® DIAPHRAGM
SHUT OFF VALVE
TURRET NOZZLE BODY
QUICK TEEJET®

OBSOLETE



Spraying Systems Co.®

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 1

Ref.

Data Sheet No.

DSQJ350X7-WB-AC

SHEET OF