


Pressure Range (bar)	Tip Number	Pressure (bar)	Single Tip Flow Rate (l/min)	Liters Per Hectare 50 cm Spacing						
				14 km/h	16 km/h	18 km/h	20 km/h	25 km/h	30 km/h	35 km/h
(0.7-3)	1/8K-12	1	5.47	469	410	365	328	263	219	188
		1.5	6.70	574	503	447	402	322	268	230
		2	7.73	663	580	515	464	371	309	265
		2.5	8.64	741	648	576	518	415	346	296
		3	9.47	812	710	631	568	455	379	325
(2-4)	TP8025	2	8.06	691	605	537	484	387	322	276
		2.5	9.01	772	676	601	541	432	360	309
		3	9.87	846	740	658	592	474	395	338
		3.5	10.7	917	803	713	642	514	428	367
(2-4) (0.7-3) (0.7-3)	TP8030 TK-15 1/8K-15	1	6.81	584	511	454	409	327	272	233
		1.5	8.34	715	626	556	500	400	334	286
		2	9.63	825	722	642	578	462	385	330
		2.5	10.8	926	810	720	648	518	432	370
		3	11.8	1011	885	787	708	566	472	405
(0.7-3) (0.7-3)	1/8K-18 TK-18	1	8.20	703	615	547	492	394	328	281
		1.5	10.0	857	750	667	600	480	400	343
		2	11.6	994	870	773	696	557	464	398
		2.5	13.0	1114	975	867	780	624	520	446
		3	14.2	1217	1065	947	852	682	568	487
(2-4) (0.7-3) (0.7-3)	TP8040 TK-20 1/8K-20	1	9.12	782	684	608	547	438	365	313
		1.5	11.2	960	840	747	672	538	448	384
		2	12.9	1106	968	860	774	619	516	442
		2.5	14.4	1234	1080	960	864	691	576	494
		3	15.8	1354	1185	1053	948	758	632	542
(0.7-3)	TP8050	2	16.1	1380	1208	1073	966	773	644	552
		2.5	18.0	1543	1350	1200	1080	864	720	617
		3	19.7	1689	1478	1313	1182	946	788	675
		3.5	21.3	1826	1598	1420	1278	1022	852	730
		4	22.7	1946	1703	1513	1362	1090	908	778
(0.7-3)	TK-30	1	13.7	1174	1028	913	822	658	548	470
		1.5	16.8	1440	1260	1120	1008	806	672	576
		2	19.4	1663	1455	1293	1164	931	776	665
		2.5	21.6	1851	1620	1440	1296	1037	864	741
		3	23.7	2031	1778	1580	1422	1138	948	813

Description:
APPLICATION RATES OF
THE TIPS SPECIFIED FOR
THE QJ360F MULTIPLE NOZZLE BODY
(METRIC)



Spraying Systems Co.
Spray Nozzles and Accessories
North Avenue at Schmale Rd.
P.O. Box 7900
Wheaton, IL 60189-7900

Ref:	Data Sheet Number
Revision No.	QJ360F-2M